

DWT6 10'-4500 COMPARTMENT
44,872 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
1/8	16	6 1/8	883	12 1/8	2,364	18 1/8	4,238	24 1/8	6,405
1/4	23	6 1/4	908	12 1/4	2,400	18 1/4	4,280	24 1/4	6,453
3/8	31	6 3/8	934	12 3/8	2,435	18 3/8	4,323	24 3/8	6,501
1/2	39	6 1/2	961	12 1/2	2,471	18 1/2	4,365	24 1/2	6,549
5/8	49	6 5/8	987	12 5/8	2,507	18 5/8	4,408	24 5/8	6,597
3/4	59	6 3/4	1,014	12 3/4	2,543	18 3/4	4,451	24 3/4	6,645
7/8	70	6 7/8	1,041	12 7/8	2,579	18 7/8	4,494	24 7/8	6,693
1	81	7	1,069	13	2,616	19	4,537	25	6,741
1 1/8	93	7 1/8	1,096	13 1/8	2,652	19 1/8	4,581	25 1/8	6,790
1 1/4	105	7 1/4	1,124	13 1/4	2,689	19 1/4	4,624	25 1/4	6,838
1 3/8	118	7 3/8	1,152	13 3/8	2,726	19 3/8	4,668	25 3/8	6,887
1 1/2	131	7 1/2	1,180	13 1/2	2,763	19 1/2	4,711	25 1/2	6,936
1 5/8	145	7 5/8	1,208	13 5/8	2,800	19 5/8	4,755	25 5/8	6,985
1 3/4	159	7 3/4	1,237	13 3/4	2,838	19 3/4	4,799	25 3/4	7,034
1 7/8	174	7 7/8	1,266	13 7/8	2,875	19 7/8	4,843	25 7/8	7,083
2	189	8	1,295	14	2,913	20	4,887	26	7,132
2 1/8	205	8 1/8	1,324	14 1/8	2,951	20 1/8	4,931	26 1/8	7,181
2 1/4	221	8 1/4	1,354	14 1/4	2,989	20 1/4	4,976	26 1/4	7,230
2 3/8	237	8 3/8	1,383	14 3/8	3,027	20 3/8	5,020	26 3/8	7,279
2 1/2	254	8 1/2	1,413	14 1/2	3,065	20 1/2	5,065	26 1/2	7,329
2 5/8	271	8 5/8	1,443	14 5/8	3,104	20 5/8	5,109	26 5/8	7,378
2 3/4	289	8 3/4	1,474	14 3/4	3,143	20 3/4	5,154	26 3/4	7,428
2 7/8	307	8 7/8	1,504	14 7/8	3,181	20 7/8	5,199	26 7/8	7,478
3	325	9	1,535	15	3,220	21	5,244	27	7,528
3 1/8	344	9 1/8	1,566	15 1/8	3,259	21 1/8	5,289	27 1/8	7,578
3 1/4	363	9 1/4	1,597	15 1/4	3,298	21 1/4	5,335	27 1/4	7,628
3 3/8	382	9 3/8	1,628	15 3/8	3,338	21 3/8	5,380	27 3/8	7,678
3 1/2	402	9 1/2	1,660	15 1/2	3,377	21 1/2	5,425	27 1/2	7,728
3 5/8	422	9 5/8	1,691	15 5/8	3,417	21 5/8	5,471	27 5/8	7,778
3 3/4	442	9 3/4	1,723	15 3/4	3,457	21 3/4	5,517	27 3/4	7,828
3 7/8	463	9 7/8	1,755	15 7/8	3,497	21 7/8	5,563	27 7/8	7,879
4	483	10	1,788	16	3,537	22	5,608	28	7,929
4 1/8	505	10 1/8	1,820	16 1/8	3,577	22 1/8	5,654	28 1/8	7,980
4 1/4	526	10 1/4	1,853	16 1/4	3,617	22 1/4	5,701	28 1/4	8,030
4 3/8	548	10 3/8	1,886	16 3/8	3,657	22 3/8	5,747	28 3/8	8,081
4 1/2	570	10 1/2	1,919	16 1/2	3,698	22 1/2	5,793	28 1/2	8,132
4 5/8	593	10 5/8	1,952	16 5/8	3,739	22 5/8	5,840	28 5/8	8,183
4 3/4	615	10 3/4	1,985	16 3/4	3,780	22 3/4	5,886	28 3/4	8,234
4 7/8	638	10 7/8	2,019	16 7/8	3,821	22 7/8	5,933	28 7/8	8,285
5	661	11	2,053	17	3,862	23	5,980	29	8,336
5 1/8	685	11 1/8	2,086	17 1/8	3,903	23 1/8	6,027	29 1/8	8,387
5 1/4	709	11 1/4	2,121	17 1/4	3,944	23 1/4	6,073	29 1/4	8,439
5 3/8	733	11 3/8	2,155	17 3/8	3,986	23 3/8	6,121	29 3/8	8,490
5 1/2	757	11 1/2	2,189	17 1/2	4,028	23 1/2	6,168	29 1/2	8,542
5 5/8	782	11 5/8	2,224	17 5/8	4,069	23 5/8	6,215	29 5/8	8,593
5 3/4	807	11 3/4	2,259	17 3/4	4,111	23 3/4	6,262	29 3/4	8,645
5 7/8	832	11 7/8	2,294	17 7/8	4,153	23 7/8	6,310	29 7/8	8,697
6	857	12	2,329	18	4,196	24	6,357	30	8,748

DWT6 10'-4500 COMPARTMENT
44,872 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
30 1/8	8,800	36 1/8	11,373	42 1/8	14,080	48 1/8	16,884	54 1/8	19,751
30 1/4	8,852	36 1/4	11,428	42 1/4	14,137	48 1/4	16,943	54 1/4	19,811
30 3/8	8,904	36 3/8	11,483	42 3/8	14,195	48 3/8	17,003	54 3/8	19,871
30 1/2	8,956	36 1/2	11,538	42 1/2	14,252	48 1/2	17,062	54 1/2	19,932
30 5/8	9,008	36 5/8	11,594	42 5/8	14,310	48 5/8	17,121	54 5/8	19,992
30 3/4	9,061	36 3/4	11,649	42 3/4	14,368	48 3/4	17,180	54 3/4	20,052
30 7/8	9,113	36 7/8	11,704	42 7/8	14,426	48 7/8	17,240	54 7/8	20,112
31	9,165	37	11,760	43	14,483	49	17,299	55	20,173
31 1/8	9,218	37 1/8	11,815	43 1/8	14,541	49 1/8	17,358	55 1/8	20,233
31 1/4	9,270	37 1/4	11,871	43 1/4	14,599	49 1/4	17,418	55 1/4	20,293
31 3/8	9,323	37 3/8	11,927	43 3/8	14,657	49 3/8	17,477	55 3/8	20,353
31 1/2	9,376	37 1/2	11,982	43 1/2	14,715	49 1/2	17,537	55 1/2	20,414
31 5/8	9,428	37 5/8	12,038	43 5/8	14,773	49 5/8	17,596	55 5/8	20,474
31 3/4	9,481	37 3/4	12,094	43 3/4	14,831	49 3/4	17,656	55 3/4	20,534
31 7/8	9,534	37 7/8	12,150	43 7/8	14,889	49 7/8	17,715	55 7/8	20,594
32	9,587	38	12,206	44	14,947	50	17,775	56	20,655
32 1/8	9,640	38 1/8	12,262	44 1/8	15,005	50 1/8	17,834	56 1/8	20,715
32 1/4	9,693	38 1/4	12,318	44 1/4	15,064	50 1/4	17,894	56 1/4	20,775
32 3/8	9,746	38 3/8	12,374	44 3/8	15,122	50 3/8	17,954	56 3/8	20,836
32 1/2	9,800	38 1/2	12,430	44 1/2	15,180	50 1/2	18,013	56 1/2	20,896
32 5/8	9,853	38 5/8	12,486	44 5/8	15,238	50 5/8	18,073	56 5/8	20,956
32 3/4	9,906	38 3/4	12,543	44 3/4	15,297	50 3/4	18,133	56 3/4	21,017
32 7/8	9,960	38 7/8	12,599	44 7/8	15,355	50 7/8	18,192	56 7/8	21,077
33	10,013	39	12,655	45	15,414	51	18,252	57	21,138
33 1/8	10,067	39 1/8	12,712	45 1/8	15,472	51 1/8	18,312	57 1/8	21,198
33 1/4	10,121	39 1/4	12,768	45 1/4	15,530	51 1/4	18,372	57 1/4	21,258
33 3/8	10,174	39 3/8	12,825	45 3/8	15,589	51 3/8	18,431	57 3/8	21,319
33 1/2	10,228	39 1/2	12,881	45 1/2	15,647	51 1/2	18,491	57 1/2	21,379
33 5/8	10,282	39 5/8	12,938	45 5/8	15,706	51 5/8	18,551	57 5/8	21,439
33 3/4	10,336	39 3/4	12,994	45 3/4	15,765	51 3/4	18,611	57 3/4	21,500
33 7/8	10,390	39 7/8	13,051	45 7/8	15,823	51 7/8	18,671	57 7/8	21,560
34	10,444	40	13,108	46	15,882	52	18,731	58	21,621
34 1/8	10,498	40 1/8	13,165	46 1/8	15,941	52 1/8	18,791	58 1/8	21,681
34 1/4	10,552	40 1/4	13,222	46 1/4	15,999	52 1/4	18,850	58 1/4	21,741
34 3/8	10,607	40 3/8	13,278	46 3/8	16,058	52 3/8	18,910	58 3/8	21,802
34 1/2	10,661	40 1/2	13,335	46 1/2	16,117	52 1/2	18,970	58 1/2	21,862
34 5/8	10,715	40 5/8	13,392	46 5/8	16,176	52 5/8	19,030	58 5/8	21,923
34 3/4	10,770	40 3/4	13,449	46 3/4	16,235	52 3/4	19,090	58 3/4	21,983
34 7/8	10,824	40 7/8	13,506	46 7/8	16,294	52 7/8	19,150	58 7/8	22,044
35	10,879	41	13,564	47	16,352	53	19,210	59	22,104
35 1/8	10,933	41 1/8	13,621	47 1/8	16,411	53 1/8	19,270	59 1/8	22,165
35 1/4	10,988	41 1/4	13,678	47 1/4	16,470	53 1/4	19,330	59 1/4	22,225
35 3/8	11,043	41 3/8	13,735	47 3/8	16,529	53 3/8	19,390	59 3/8	22,285
35 1/2	11,098	41 1/2	13,793	47 1/2	16,588	53 1/2	19,451	59 1/2	22,346
35 5/8	11,152	41 5/8	13,850	47 5/8	16,648	53 5/8	19,511	59 5/8	22,406
35 3/4	11,207	41 3/4	13,907	47 3/4	16,707	53 3/4	19,571	59 3/4	22,467
35 7/8	11,262	41 7/8	13,965	47 7/8	16,766	53 7/8	19,631	59 7/8	22,527
36	11,317	42	14,022	48	16,825	54	19,691	60	22,588

DWT6 10'-4500 COMPARTMENT
44,872 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
60 1/8	22,648	66 1/8	25,543	72 1/8	28,403	78 1/8	31,195	84 1/8	33,885
60 1/4	22,708	66 1/4	25,603	72 1/4	28,462	78 1/4	31,252	84 1/4	33,940
60 3/8	22,769	66 3/8	25,663	72 3/8	28,520	78 3/8	31,309	84 3/8	33,994
60 1/2	22,829	66 1/2	25,723	72 1/2	28,579	78 1/2	31,366	84 1/2	34,049
60 5/8	22,890	66 5/8	25,783	72 5/8	28,638	78 5/8	31,424	84 5/8	34,103
60 3/4	22,950	66 3/4	25,843	72 3/4	28,697	78 3/4	31,481	84 3/4	34,158
60 7/8	23,011	66 7/8	25,903	72 7/8	28,756	78 7/8	31,538	84 7/8	34,212
61	23,071	67	25,963	73	28,815	79	31,595	85	34,266
61 1/8	23,131	67 1/8	26,022	73 1/8	28,874	79 1/8	31,651	85 1/8	34,321
61 1/4	23,192	67 1/4	26,082	73 1/4	28,932	79 1/4	31,708	85 1/4	34,375
61 3/8	23,252	67 3/8	26,142	73 3/8	28,991	79 3/8	31,765	85 3/8	34,429
61 1/2	23,313	67 1/2	26,202	73 1/2	29,050	79 1/2	31,822	85 1/2	34,483
61 5/8	23,373	67 5/8	26,262	73 5/8	29,108	79 5/8	31,878	85 5/8	34,537
61 3/4	23,434	67 3/4	26,322	73 3/4	29,167	79 3/4	31,935	85 3/4	34,591
61 7/8	23,494	67 7/8	26,382	73 7/8	29,226	79 7/8	31,992	85 7/8	34,645
62	23,554	68	26,442	74	29,284	80	32,048	86	34,699
62 1/8	23,615	68 1/8	26,501	74 1/8	29,343	80 1/8	32,105	86 1/8	34,752
62 1/4	23,675	68 1/4	26,561	74 1/4	29,401	80 1/4	32,161	86 1/4	34,806
62 3/8	23,735	68 3/8	26,621	74 3/8	29,459	80 3/8	32,218	86 3/8	34,860
62 1/2	23,796	68 1/2	26,681	74 1/2	29,518	80 1/2	32,274	86 1/2	34,913
62 5/8	23,856	68 5/8	26,740	74 5/8	29,576	80 5/8	32,330	86 5/8	34,967
62 3/4	23,917	68 3/4	26,800	74 3/4	29,635	80 3/4	32,387	86 3/4	35,020
62 7/8	23,977	68 7/8	26,860	74 7/8	29,693	80 7/8	32,443	86 7/8	35,073
63	24,037	69	26,919	75	29,751	81	32,499	87	35,127
63 1/8	24,098	69 1/8	26,979	75 1/8	29,809	81 1/8	32,555	87 1/8	35,180
63 1/4	24,158	69 1/4	27,039	75 1/4	29,868	81 1/4	32,611	87 1/4	35,233
63 3/8	24,218	69 3/8	27,098	75 3/8	29,926	81 3/8	32,667	87 3/8	35,286
63 1/2	24,279	69 1/2	27,158	75 1/2	29,984	81 1/2	32,723	87 1/2	35,339
63 5/8	24,339	69 5/8	27,217	75 5/8	30,042	81 5/8	32,779	87 5/8	35,392
63 3/4	24,399	69 3/4	27,277	75 3/4	30,100	81 3/4	32,835	87 3/4	35,445
63 7/8	24,459	69 7/8	27,336	75 7/8	30,158	81 7/8	32,891	87 7/8	35,497
64	24,520	70	27,396	76	30,216	82	32,946	88	35,550
64 1/8	24,580	70 1/8	27,455	76 1/8	30,274	82 1/8	33,002	88 1/8	35,603
64 1/4	24,640	70 1/4	27,514	76 1/4	30,332	82 1/4	33,058	88 1/4	35,655
64 3/8	24,700	70 3/8	27,574	76 3/8	30,390	82 3/8	33,113	88 3/8	35,708
64 1/2	24,761	70 1/2	27,633	76 1/2	30,447	82 1/2	33,169	88 1/2	35,760
64 5/8	24,821	70 5/8	27,693	76 5/8	30,505	82 5/8	33,224	88 5/8	35,812
64 3/4	24,881	70 3/4	27,752	76 3/4	30,563	82 3/4	33,279	88 3/4	35,865
64 7/8	24,941	70 7/8	27,811	76 7/8	30,620	82 7/8	33,335	88 7/8	35,917
65	25,001	71	27,870	77	30,678	83	33,390	89	35,969
65 1/8	25,062	71 1/8	27,930	77 1/8	30,736	83 1/8	33,445	89 1/8	36,021
65 1/4	25,122	71 1/4	27,989	77 1/4	30,793	83 1/4	33,500	89 1/4	36,073
65 3/8	25,182	71 3/8	28,048	77 3/8	30,851	83 3/8	33,556	89 3/8	36,125
65 1/2	25,242	71 1/2	28,107	77 1/2	30,908	83 1/2	33,611	89 1/2	36,176
65 5/8	25,302	71 5/8	28,166	77 5/8	30,966	83 5/8	33,666	89 5/8	36,228
65 3/4	25,362	71 3/4	28,225	77 3/4	31,023	83 3/4	33,720	89 3/4	36,280
65 7/8	25,422	71 7/8	28,285	77 7/8	31,080	83 7/8	33,775	89 7/8	36,331
66	25,482	72	28,344	78	31,138	84	33,830	90	36,383

DWT6 10'-4500 COMPARTMENT
44,872 Gallons

06/22/2023

DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)	DIPSTICK (in)	VOLUME (gal)
90 1/8	36,434	96 1/8	38,799	102 1/8	40,929	108 1/8	42,752	114 1/8	44,164
90 1/4	36,486	96 1/4	38,846	102 1/4	40,970	108 1/4	42,787	114 1/4	44,188
90 3/8	36,537	96 3/8	38,893	102 3/8	41,011	108 3/8	42,820	114 3/8	44,212
90 1/2	36,588	96 1/2	38,940	102 1/2	41,052	108 1/2	42,854	114 1/2	44,235
90 5/8	36,639	96 5/8	38,987	102 5/8	41,093	108 5/8	42,888	114 5/8	44,258
90 3/4	36,690	96 3/4	39,033	102 3/4	41,134	108 3/4	42,921	114 3/4	44,280
90 7/8	36,741	96 7/8	39,080	102 7/8	41,175	108 7/8	42,954	114 7/8	44,303
91	36,792	97	39,126	103	41,215	109	42,987	115	44,325
91 1/8	36,842	97 1/8	39,172	103 1/8	41,256	109 1/8	43,020	115 1/8	44,347
91 1/4	36,893	97 1/4	39,218	103 1/4	41,296	109 1/4	43,053	115 1/4	44,368
91 3/8	36,944	97 3/8	39,264	103 3/8	41,336	109 3/8	43,085	115 3/8	44,390
91 1/2	36,994	97 1/2	39,310	103 1/2	41,376	109 1/2	43,118	115 1/2	44,410
91 5/8	37,045	97 5/8	39,356	103 5/8	41,416	109 5/8	43,150	115 5/8	44,431
91 3/4	37,095	97 3/4	39,402	103 3/4	41,456	109 3/4	43,182	115 3/4	44,451
91 7/8	37,145	97 7/8	39,448	103 7/8	41,496	109 7/8	43,213	115 7/8	44,471
92	37,195	98	39,493	104	41,535	110	43,245	116	44,491
92 1/8	37,245	98 1/8	39,538	104 1/8	41,575	110 1/8	43,276	116 1/8	44,510
92 1/4	37,295	98 1/4	39,584	104 1/4	41,614	110 1/4	43,307	116 1/4	44,529
92 3/8	37,345	98 3/8	39,629	104 3/8	41,653	110 3/8	43,338	116 3/8	44,548
92 1/2	37,395	98 1/2	39,674	104 1/2	41,692	110 1/2	43,369	116 1/2	44,566
92 5/8	37,445	98 5/8	39,719	104 5/8	41,730	110 5/8	43,399	116 5/8	44,584
92 3/4	37,494	98 3/4	39,764	104 3/4	41,769	110 3/4	43,430	116 3/4	44,602
92 7/8	37,544	98 7/8	39,808	104 7/8	41,807	110 7/8	43,460	116 7/8	44,619
93	37,593	99	39,853	105	41,846	111	43,490	117	44,636
93 1/8	37,643	99 1/8	39,897	105 1/8	41,884	111 1/8	43,519	117 1/8	44,652
93 1/4	37,692	99 1/4	39,942	105 1/4	41,922	111 1/4	43,549	117 1/4	44,668
93 3/8	37,741	99 3/8	39,986	105 3/8	41,960	111 3/8	43,578	117 3/8	44,684
93 1/2	37,790	99 1/2	40,030	105 1/2	41,998	111 1/2	43,607	117 1/2	44,699
93 5/8	37,839	99 5/8	40,074	105 5/8	42,035	111 5/8	43,636	117 5/8	44,714
93 3/4	37,888	99 3/4	40,118	105 3/4	42,072	111 3/4	43,665	117 3/4	44,728
93 7/8	37,937	99 7/8	40,162	105 7/8	42,110	111 7/8	43,693	117 7/8	44,742
94	37,986	100	40,205	106	42,147	112	43,721	118	44,755
94 1/8	38,034	100 1/8	40,249	106 1/8	42,184	112 1/8	43,749	118 1/8	44,768
94 1/4	38,083	100 1/4	40,292	106 1/4	42,221	112 1/4	43,777	118 1/4	44,780
94 3/8	38,131	100 3/8	40,336	106 3/8	42,257	112 3/8	43,804	118 3/8	44,792
94 1/2	38,180	100 1/2	40,379	106 1/2	42,294	112 1/2	43,832	118 1/2	44,803
94 5/8	38,228	100 5/8	40,422	106 5/8	42,330	112 5/8	43,859	118 5/8	44,814
94 3/4	38,276	100 3/4	40,465	106 3/4	42,366	112 3/4	43,886	118 3/4	44,824
94 7/8	38,324	100 7/8	40,508	106 7/8	42,402	112 7/8	43,912	118 7/8	44,834
95	38,372	101	40,550	107	42,438	113	43,938	119	44,842
95 1/8	38,420	101 1/8	40,593	107 1/8	42,473	113 1/8	43,965	119 1/8	44,850
95 1/4	38,468	101 1/4	40,635	107 1/4	42,509	113 1/4	43,990	119 1/4	44,857
95 3/8	38,516	101 3/8	40,677	107 3/8	42,544	113 3/8	44,016	119 3/8	44,863
95 1/2	38,563	101 1/2	40,720	107 1/2	42,579	113 1/2	44,041	119 1/2	44,868
95 5/8	38,611	101 5/8	40,762	107 5/8	42,614	113 5/8	44,066	119 5/8	44,872
95 3/4	38,658	101 3/4	40,804	107 3/4	42,649	113 3/4	44,091		
95 7/8	38,705	101 7/8	40,845	107 7/8	42,684	113 7/8	44,116		
96	38,752	102	40,887	108	42,718	114	44,140		

Fiber Glass Systems



HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

Kolor Kut Water Finding Paste Description - PASTE02 - for Salt and Chloride Solutions
7915 East Elm Street
Houston, TX 77012
Phone (713) 926-4780
E-Mail Sales@KolorKut.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

NOV - Fiber Glass Systems - Containment Solutions™ Tanks

500 Conroe Park Drive West
Conroe, TX 77303
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.