

Lube Cube® lube oil tanks are the best solution for storage of new and used lubrication oils. Lube Cubes provide lower installed costs than underground tanks, better space utilization than cylindrical aboveground tanks and lower operation costs than 55-gallon drums.

Lube Cube Tanks are designed for easy and convenient installation either indoors, in service bays or basements, or outdoors, next to the building. Lube Cube's rectangular shape allows for the storage of up to 20% more volume in a given space than comparable cylindrical tank capacities.

Lube Cubes are available as either single or double-wall tanks. Double-wall tanks are UL listed as integral secondary containment, and therefore do not require dikes for leak containment.

Desert Sand epoxy finish is standard. Special colors, coatings and interior linings, custom dimensions and equipment packages are available upon request.



Standard features

- UL-142 listed
- · Meets NFPA 30 Standard
- Skid mounted for easy installation
- · Corrosion resistant exterior coating
- Moveable by forklift
- NPT fittings with PVC plugs
 Single-Wall: 5 (plus emergency vent opening)
 Double-Wall: above fittings (plus emergency vent and additional openings)
- Lifting lugs

Options

- 7 gallon spill box
- Custom sizes
- Compartments available
- Stainless-steel construction
- · Internal linings
- Equipment packages

Lube Cube tanks are available in standard sizes from 60 to 20,000 gallons.

Lube Cube Multi-Purpose Tanks

Standard Tank Sizes

Capacity (gallons)	Dimensions (L x W x H)	Weight (lbs)	Capacity (Gallons)	Dimensions (L x W x H)	Weight (lbs)
60	1 ft. 11 in. x 2 ft. 10 in. x 3 ft. 1 in.	395	480	5 ft. 8 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,350
90	2 ft. 6 in. x 2 ft. 10 in. x 3 ft. 1 in.	485	500	4 ft. 10 in. x 3 ft. 10 in. x 5 ft. 1 in.	1,315
120	3 ft. 2 in. x 2 ft. 10 in. x 3 ft. 1 in.	565	550	5 ft. 2 in. x 3 ft. 10 in. x 5 ft.1 in.	1,380
150	3 ft. 9 in. x 2 ft. 10 in. x 3 ft. 1 in.	650	600	5 ft. 7 in. x 3 ft. 10 in. x 5 ft. 1 in.	1,450
150	2 ft. 10 in. x 2 ft. 10 in. x 4 ft. 1 in.	645	650	6 ft. 3 in. x 3 ft. 10 in. x 5 ft. 1 in.	1,525
180	3 ft. 4 in. x 2 ft. 10 in. x 4 ft. 1 in.	725	750	6 ft. 9 in. x 4 ft. 0 in. x 5 ft. 1 in.	1,760
200	3 ft. 7 in. x 2 ft. 10 in. x 4 ft. 1 in.	735	1,000	9 ft. 4 in. x 4 ft. 0 in. x 5 ft. 1 in.	2,400
210	3 ft. 9 in. x 2 ft. 10 in. x 4 ft. 1 in.	785	1,500	13 ft. 4 in. x 4 ft. 0 in. x 5 ft. 1 in.	3,250
225	3 ft. 11 in. x 2 ft. 10 in. x 4 ft. 1 in.	815	2,000	13 ft. 9 in. x 5 ft. 0 in. x 5 ft. 1 in.	3,800
240	4 ft. 2 in. x 2 ft. 10 in. x 4 ft. 1 in.	850	2,500	17 ft. 0 in. x 5 ft. 0 in. x 5 ft. 1 in.	4,500
250	4 ft. 4 in. x 2 ft. 10 in. x 4 ft. 1 in.	875	3,000	20 ft. 5 in. x 5 ft. 0 in. x 5 ft. 1 in.	6,650
275	4 ft. 8 in. x 2 ft. 10 in. x 4 ft. 1 in.	925	4,000	22 ft. 3 in. x 5 ft. 0 in. x 6 ft. 1 in.	8,150
280	4 ft. 10 in. x 2 ft. 10 in. x 4 ft. 1 in.	945	5,000	17 ft. 1 in. x 8 ft. 0 in. x 6 ft. 1 in.	10,150
300	3 ft. 10 in. x 3 ft. 10 in. x 4 ft. 1 in.	960	6,000	20 ft. 3 in. x 8 ft. 0 in. x 6 ft. 1 in.	11,400
325	4 ft. 1 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,000	8,000	19 ft. 11 in. x 8 ft. 0 in. x 8 ft. 1 in.	14,000
350	4 ft. 4 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,050	10,000	24 ft. 7 in. x 8 ft. 0 in. x 8 ft. 1 in.	16,125
375	4 ft. 7 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,090	12,000	29 ft. 3 in. x 8 ft. 0 in. x 8 ft. 1 in.	18,550
400	4 ft. 10 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,130	15,000	36 ft. 3 in. x 8 ft. 0 in. x 8 ft. 1 in.	22,100
450	5 ft. 5 in. x 3 ft. 10 in. x 4 ft. 1 in.	1,230	20,000	48 ft. 2 in. x 8 ft. 0 in. x 8 ft. 1 in.	28,900

Standard Equipment

- A. Primary Tank
- **B.** Secondary Tank (with corrosion resistant Desert Sand epoxy exterior coating)
- **C.** Lifting Lugs:
 - (2) 60 650 Gallon
 - (4) 1,000 20,000 Gallon
- **D.** Support Feet
- **E**⋅ ½ in. NPT Drain with optional spill box
- **F.** Fill 2, 4 or 6 in.
- **G.** Primary Tank Emergency Vent 4, 6, 8, or 10 in.
- **H.** Secondary Containment Emergency Vent 4, 6, 8 or 10 in.
- **I.** 2 in. Primary Working Vent
- J. 2 in. Secondary Containment Working Vent
- K. 2 in. Gauge
- L. 2 in. Monitoring Point
- M. 2 in. Spare
- N. 2 or 4 in. Spare

