

Model DWT6 (6) 10000 L
DW FRP CUL Tank = 10,111Liters

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	10	30.5	1145	60.5	2959	90.5	5041	120.5	7125
1.0	17	31.0	1172	61.0	2992	91.0	5077	121.0	7158
1.5	24	31.5	1198	61.5	3026	91.5	5112	121.5	7191
2.0	32	32.0	1225	62.0	3059	92.0	5148	122.0	7224
2.5	41	32.5	1252	62.5	3092	92.5	5183	122.5	7257
3.0	51	33.0	1279	63.0	3126	93.0	5219	123.0	7290
3.5	61	33.5	1306	63.5	3159	93.5	5254	123.5	7323
4.0	72	34.0	1334	64.0	3193	94.0	5290	124.0	7355
4.5	83	34.5	1361	64.5	3227	94.5	5325	124.5	7388
5.0	95	35.0	1389	65.0	3260	95.0	5361	125.0	7421
5.5	108	35.5	1417	65.5	3294	95.5	5396	125.5	7453
6.0	121	36.0	1445	66.0	3328	96.0	5431	126.0	7485
6.5	134	36.5	1473	66.5	3362	96.5	5467	126.5	7518
7.0	148	37.0	1502	67.0	3396	97.0	5502	127.0	7550
7.5	162	37.5	1530	67.5	3430	97.5	5538	127.5	7582
8.0	177	38.0	1559	68.0	3464	98.0	5573	128.0	7614
8.5	192	38.5	1587	68.5	3498	98.5	5608	128.5	7646
9.0	208	39.0	1616	69.0	3533	99.0	5644	129.0	7678
9.5	224	39.5	1645	69.5	3567	99.5	5679	129.5	7710
10.0	240	40.0	1674	70.0	3601	100.0	5714	130.0	7742
10.5	257	40.5	1703	70.5	3636	100.5	5750	130.5	7773
11.0	274	41.0	1733	71.0	3670	101.0	5785	131.0	7805
11.5	291	41.5	1762	71.5	3705	101.5	5820	131.5	7836
12.0	309	42.0	1792	72.0	3739	102.0	5855	132.0	7867
12.5	327	42.5	1822	72.5	3774	102.5	5890	132.5	7899
13.0	345	43.0	1852	73.0	3808	103.0	5925	133.0	7930
13.5	364	43.5	1882	73.5	3843	103.5	5961	133.5	7961
14.0	383	44.0	1912	74.0	3878	104.0	5996	134.0	7992
14.5	402	44.5	1942	74.5	3913	104.5	6031	134.5	8023
15.0	422	45.0	1972	75.0	3947	105.0	6066	135.0	8053
15.5	442	45.5	2003	75.5	3982	105.5	6101	135.5	8084
16.0	462	46.0	2033	76.0	4017	106.0	6135	136.0	8114
16.5	482	46.5	2064	76.5	4052	106.5	6170	136.5	8145
17.0	503	47.0	2094	77.0	4087	107.0	6205	137.0	8175
17.5	524	47.5	2125	77.5	4122	107.5	6240	137.5	8205
18.0	545	48.0	2156	78.0	4157	108.0	6275	138.0	8235
18.5	566	48.5	2187	78.5	4192	108.5	6309	138.5	8265
19.0	588	49.0	2218	79.0	4227	109.0	6344	139.0	8295
19.5	610	49.5	2250	79.5	4263	109.5	6379	139.5	8325
20.0	632	50.0	2281	80.0	4298	110.0	6413	140.0	8355
20.5	654	50.5	2313	80.5	4333	110.5	6448	140.5	8384
21.0	677	51.0	2344	81.0	4368	111.0	6482	141.0	8413
21.5	700	51.5	2376	81.5	4404	111.5	6516	141.5	8443
22.0	723	52.0	2407	82.0	4439	112.0	6551	142.0	8472
22.5	746	52.5	2439	82.5	4474	112.5	6585	142.5	8501
23.0	769	53.0	2471	83.0	4509	113.0	6619	143.0	8529
23.5	793	53.5	2503	83.5	4545	113.5	6653	143.5	8558
24.0	817	54.0	2535	84.0	4580	114.0	6688	144.0	8587
24.5	841	54.5	2567	84.5	4616	114.5	6722	144.5	8615
25.0	865	55.0	2600	85.0	4651	115.0	6756	145.0	8643
25.5	890	55.5	2632	85.5	4686	115.5	6789	145.5	8672
26.0	915	56.0	2664	86.0	4722	116.0	6823	146.0	8700
26.5	939	56.5	2697	86.5	4757	116.5	6857	146.5	8727
27.0	965	57.0	2729	87.0	4793	117.0	6891	147.0	8755
27.5	990	57.5	2762	87.5	4828	117.5	6925	147.5	8783
28.0	1015	58.0	2795	88.0	4864	118.0	6958	148.0	8810
28.5	1041	58.5	2827	88.5	4899	118.5	6992	148.5	8837
29.0	1067	59.0	2860	89.0	4935	119.0	7025	149.0	8864
29.5	1093	59.5	2893	89.5	4970	119.5	7058	149.5	8891
30.0	1119	60.0	2926	90.0	5006	120.0	7092	150.0	8918

**Model DWT6 (6) 10000 L
DW FRP CUL Tank = 10,111Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
150.5	8945	180.5	10096
151.0	8971	181.0	10102
151.5	8998	181.5	10107
152.0	9024	182.0	10111
152.5	9050		
153.0	9075		
153.5	9101		
154.0	9126		
154.5	9152		
155.0	9177		
155.5	9201		
156.0	9226		
156.5	9251		
157.0	9275		
157.5	9299		
158.0	9323		
158.5	9346		
159.0	9370		
159.5	9393		
160.0	9416		
160.5	9439		
161.0	9461		
161.5	9484		
162.0	9506		
162.5	9528		
163.0	9549		
163.5	9571		
164.0	9592		
164.5	9612		
165.0	9633		
165.5	9653		
166.0	9673		
166.5	9693		
167.0	9713		
167.5	9732		
168.0	9751		
168.5	9769		
169.0	9788		
169.5	9806		
170.0	9823		
170.5	9841		
171.0	9858		
171.5	9874		
172.0	9891		
172.5	9906		
173.0	9922		
173.5	9937		
174.0	9952		
174.5	9966		
175.0	9980		
175.5	9993		
176.0	10006		
176.5	10019		
177.0	10031		
177.5	10042		
178.0	10053		
178.5	10063		
179.0	10072		
179.5	10081		
180.0	10089		



**CONTAINMENT
SOLUTIONS®**

HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection:

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste
Federal Process Corp.
800-846-7325
www.gasoila.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

Containment Solutions, Inc.
333 North Rivershire Dr., Suite 190
Conroe, TX 77304
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.

Pub No. CAL 6-10000DWT-CAN 5/11