

**4'-1000 DWT6 Double-Wall Tank
966 Gals**

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
1/8	1	6 1/8	73	12 1/8	194	18 1/8	339	24 1/8	494
1/4	2	6 1/4	75	12 1/4	196	18 1/4	342	24 1/4	498
3/8	3	6 3/8	78	12 3/8	199	18 3/8	345	24 3/8	501
1/2	3	6 1/2	80	12 1/2	202	18 1/2	348	24 1/2	504
5/8	4	6 5/8	82	12 5/8	205	18 5/8	351	24 5/8	508
3/4	5	6 3/4	84	12 3/4	208	18 3/4	355	24 3/4	511
7/8	6	6 7/8	86	12 7/8	211	18 7/8	358	24 7/8	514
1	7	7	89	13	214	19	361	25	517
1 1/8	8	7 1/8	91	13 1/8	216	19 1/8	364	25 1/8	521
1 1/4	9	7 1/4	93	13 1/4	219	19 1/4	367	25 1/4	524
1 3/8	10	7 3/8	95	13 3/8	222	19 3/8	371	25 3/8	527
1 1/2	11	7 1/2	98	13 1/2	225	19 1/2	374	25 1/2	530
1 5/8	12	7 5/8	100	13 5/8	228	19 5/8	377	25 5/8	534
1 3/4	13	7 3/4	102	13 3/4	231	19 3/4	380	25 3/4	537
1 7/8	14	7 7/8	105	13 7/8	234	19 7/8	383	25 7/8	540
2	16	8	107	14	237	20	387	26	544
2 1/8	17	8 1/8	110	14 1/8	240	20 1/8	390	26 1/8	547
2 1/4	18	8 1/4	112	14 1/4	243	20 1/4	393	26 1/4	550
2 3/8	20	8 3/8	114	14 3/8	246	20 3/8	396	26 3/8	553
2 1/2	21	8 1/2	117	14 1/2	249	20 1/2	400	26 1/2	557
2 5/8	23	8 5/8	119	14 5/8	252	20 5/8	403	26 5/8	560
2 3/4	24	8 3/4	122	14 3/4	255	20 3/4	406	26 3/4	563
2 7/8	25	8 7/8	124	14 7/8	258	20 7/8	409	26 7/8	566
3	27	9	127	15	261	21	413	27	570
3 1/8	29	9 1/8	129	15 1/8	264	21 1/8	416	27 1/8	573
3 1/4	30	9 1/4	132	15 1/4	267	21 1/4	419	27 1/4	576
3 3/8	32	9 3/8	134	15 3/8	270	21 3/8	422	27 3/8	579
3 1/2	33	9 1/2	137	15 1/2	273	21 1/2	426	27 1/2	583
3 5/8	35	9 5/8	140	15 5/8	276	21 5/8	429	27 5/8	586
3 3/4	37	9 3/4	142	15 3/4	279	21 3/4	432	27 3/4	589
3 7/8	38	9 7/8	145	15 7/8	282	21 7/8	436	27 7/8	592
4	40	10	147	16	285	22	439	28	595
4 1/8	42	10 1/8	150	16 1/8	288	22 1/8	442	28 1/8	599
4 1/4	44	10 1/4	153	16 1/4	292	22 1/4	445	28 1/4	602
4 3/8	46	10 3/8	155	16 3/8	295	22 3/8	449	28 3/8	605
4 1/2	47	10 1/2	158	16 1/2	298	22 1/2	452	28 1/2	608
4 5/8	49	10 5/8	161	16 5/8	301	22 5/8	455	28 5/8	611
4 3/4	51	10 3/4	163	16 3/4	304	22 3/4	458	28 3/4	615
4 7/8	53	10 7/8	166	16 7/8	307	22 7/8	462	28 7/8	618
5	55	11	169	17	310	23	465	29	621
5 1/8	57	11 1/8	171	17 1/8	313	23 1/8	468	29 1/8	624
5 1/4	59	11 1/4	174	17 1/4	316	23 1/4	472	29 1/4	627
5 3/8	61	11 3/8	177	17 3/8	320	23 3/8	475	29 3/8	631
5 1/2	63	11 1/2	180	17 1/2	323	23 1/2	478	29 1/2	634
5 5/8	65	11 5/8	182	17 5/8	326	23 5/8	481	29 5/8	637
5 3/4	67	11 3/4	185	17 3/4	329	23 3/4	485	29 3/4	640
5 7/8	69	11 7/8	188	17 7/8	332	23 7/8	488	29 7/8	643
6	71	12	191	18	335	24	491	30	646

4'-1000 DWT6 Double-Wall Tank 966 Gals

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
30 1/8	650	36 1/8	792	42 1/8	907
30 1/4	653	36 1/4	795	42 1/4	909
30 3/8	656	36 3/8	797	42 3/8	911
30 1/2	659	36 1/2	800	42 1/2	913
30 5/8	662	36 5/8	803	42 5/8	915
30 3/4	665	36 3/4	805	42 3/4	917
30 7/8	668	36 7/8	808	42 7/8	919
31	671	37	811	43	920
31 1/8	674	37 1/8	813	43 1/8	922
31 1/4	678	37 1/4	816	43 1/4	924
31 3/8	681	37 3/8	819	43 3/8	926
31 1/2	684	37 1/2	821	43 1/2	928
31 5/8	687	37 5/8	824	43 5/8	929
31 3/4	690	37 3/4	826	43 3/4	931
31 7/8	693	37 7/8	829	43 7/8	933
32	696	38	832	44	934
32 1/8	699	38 1/8	834	44 1/8	936
32 1/4	702	38 1/4	837	44 1/4	937
32 3/8	705	38 3/8	839	44 3/8	939
32 1/2	708	38 1/2	842	44 1/2	941
32 5/8	711	38 5/8	844	44 5/8	942
32 3/4	714	38 3/4	847	44 3/4	943
32 7/8	717	38 7/8	849	44 7/8	945
33	720	39	852	45	946
33 1/8	723	39 1/8	854	45 1/8	948
33 1/4	726	39 1/4	856	45 1/4	949
33 3/8	729	39 3/8	859	45 3/8	950
33 1/2	732	39 1/2	861	45 1/2	952
33 5/8	735	39 5/8	864	45 5/8	953
33 3/4	738	39 3/4	866	45 3/4	954
33 7/8	741	39 7/8	868	45 7/8	955
34	744	40	871	46	956
34 1/8	747	40 1/8	873	46 1/8	957
34 1/4	750	40 1/4	875	46 1/4	958
34 3/8	752	40 3/8	877	46 3/8	959
34 1/2	755	40 1/2	880	46 1/2	960
34 5/8	758	40 5/8	882	46 5/8	961
34 3/4	761	40 3/4	884	46 3/4	962
34 7/8	764	40 7/8	886	46 7/8	963
35	767	41	888	47	963
35 1/8	770	41 1/8	891	47 1/8	964
35 1/4	772	41 1/4	893	47 1/4	965
35 3/8	775	41 3/8	895	47 3/8	965
35 1/2	778	41 1/2	897	47 1/2	966
35 5/8	781	41 5/8	899	47 5/8	966
35 3/4	784	41 3/4	901		
35 7/8	786	41 7/8	903		
36	789	42	905		



CONTAINMENT
SOLUTIONS®

HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

WATER FINDER #7686-1870
DAYCO/NATIONAL
DAYTON, OH
TEL: 1-800-283-2926
FAX: 1-800-688-4854

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

ContainmentSolutions, Inc.
5150 Jefferson Chemical Road
Conroe, TX 77301
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.