

**4'-1500 DWT6 Double-Wall Tank  
1514 Gals**

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
1/8	2	6 1/8	117	12 1/8	306	18 1/8	533	24 1/8	775
1/4	3	6 1/4	120	12 1/4	311	18 1/4	537	24 1/4	780
3/8	4	6 3/8	124	12 3/8	315	18 3/8	542	24 3/8	785
1/2	5	6 1/2	127	12 1/2	320	18 1/2	547	24 1/2	790
5/8	7	6 5/8	131	12 5/8	324	18 5/8	552	24 5/8	795
3/4	8	6 3/4	134	12 3/4	329	18 3/4	557	24 3/4	800
7/8	9	6 7/8	138	12 7/8	333	18 7/8	562	24 7/8	805
1	11	7	141	13	338	19	567	25	811
1 1/8	12	7 1/8	145	13 1/8	342	19 1/8	572	25 1/8	816
1 1/4	14	7 1/4	149	13 1/4	347	19 1/4	577	25 1/4	821
1 3/8	16	7 3/8	152	13 3/8	351	19 3/8	582	25 3/8	826
1 1/2	18	7 1/2	156	13 1/2	356	19 1/2	587	25 1/2	831
1 5/8	19	7 5/8	159	13 5/8	360	19 5/8	592	25 5/8	836
1 3/4	21	7 3/4	163	13 3/4	365	19 3/4	597	25 3/4	841
1 7/8	23	7 7/8	167	13 7/8	370	19 7/8	602	25 7/8	846
2	25	8	171	14	374	20	607	26	851
2 1/8	27	8 1/8	174	14 1/8	379	20 1/8	612	26 1/8	856
2 1/4	30	8 1/4	178	14 1/4	383	20 1/4	617	26 1/4	861
2 3/8	32	8 3/8	182	14 3/8	388	20 3/8	622	26 3/8	866
2 1/2	34	8 1/2	186	14 1/2	393	20 1/2	628	26 1/2	871
2 5/8	36	8 5/8	190	14 5/8	397	20 5/8	633	26 5/8	877
2 3/4	39	8 3/4	194	14 3/4	402	20 3/4	638	26 3/4	882
2 7/8	41	8 7/8	198	14 7/8	407	20 7/8	643	26 7/8	887
3	44	9	202	15	412	21	648	27	892
3 1/8	46	9 1/8	205	15 1/8	416	21 1/8	653	27 1/8	897
3 1/4	49	9 1/4	209	15 1/4	421	21 1/4	658	27 1/4	902
3 3/8	51	9 3/8	213	15 3/8	426	21 3/8	663	27 3/8	907
3 1/2	54	9 1/2	217	15 1/2	430	21 1/2	668	27 1/2	912
3 5/8	56	9 5/8	222	15 5/8	435	21 5/8	673	27 5/8	917
3 3/4	59	9 3/4	226	15 3/4	440	21 3/4	678	27 3/4	922
3 7/8	62	9 7/8	230	15 7/8	445	21 7/8	683	27 7/8	927
4	65	10	234	16	450	22	688	28	932
4 1/8	67	10 1/8	238	16 1/8	454	22 1/8	693	28 1/8	937
4 1/4	70	10 1/4	242	16 1/4	459	22 1/4	699	28 1/4	942
4 3/8	73	10 3/8	246	16 3/8	464	22 3/8	704	28 3/8	947
4 1/2	76	10 1/2	250	16 1/2	469	22 1/2	709	28 1/2	952
4 5/8	79	10 5/8	255	16 5/8	474	22 5/8	714	28 5/8	957
4 3/4	82	10 3/4	259	16 3/4	479	22 3/4	719	28 3/4	962
4 7/8	85	10 7/8	263	16 7/8	483	22 7/8	724	28 7/8	967
5	88	11	267	17	488	23	729	29	972
5 1/8	91	11 1/8	272	17 1/8	493	23 1/8	734	29 1/8	977
5 1/4	94	11 1/4	276	17 1/4	498	23 1/4	739	29 1/4	982
5 3/8	97	11 3/8	280	17 3/8	503	23 3/8	744	29 3/8	987
5 1/2	101	11 1/2	284	17 1/2	508	23 1/2	749	29 1/2	992
5 5/8	104	11 5/8	289	17 5/8	513	23 5/8	755	29 5/8	996
5 3/4	107	11 3/4	293	17 3/4	518	23 3/4	760	29 3/4	1001
5 7/8	110	11 7/8	298	17 7/8	523	23 7/8	765	29 7/8	1006
6	114	12	302	18	528	24	770	30	1011

## 4'-1500 DWT6 Double-Wall Tank 1514 Gals

DIPSTICK	GALLONS	DIPSTICK	GALLONS	DIPSTICK	GALLONS
30 1/8	1016	36 1/8	1238	42 1/8	1420
30 1/4	1021	36 1/4	1243	42 1/4	1423
30 3/8	1026	36 3/8	1247	42 3/8	1426
30 1/2	1031	36 1/2	1251	42 1/2	1429
30 5/8	1036	36 5/8	1255	42 5/8	1432
30 3/4	1040	36 3/4	1260	42 3/4	1435
30 7/8	1045	36 7/8	1264	42 7/8	1438
31	1050	37	1268	43	1441
31 1/8	1055	37 1/8	1272	43 1/8	1444
31 1/4	1060	37 1/4	1276	43 1/4	1447
31 3/8	1065	37 3/8	1280	43 3/8	1450
31 1/2	1069	37 1/2	1285	43 1/2	1452
31 5/8	1074	37 5/8	1289	43 5/8	1455
31 3/4	1079	37 3/4	1293	43 3/4	1458
31 7/8	1084	37 7/8	1297	43 7/8	1460
32	1088	38	1301	44	1463
32 1/8	1093	38 1/8	1305	44 1/8	1466
32 1/4	1098	38 1/4	1309	44 1/4	1468
32 3/8	1103	38 3/8	1313	44 3/8	1471
32 1/2	1107	38 1/2	1317	44 1/2	1473
32 5/8	1112	38 5/8	1321	44 5/8	1475
32 3/4	1117	38 3/4	1324	44 3/4	1478
32 7/8	1121	38 7/8	1328	44 7/8	1480
33	1126	39	1332	45	1482
33 1/8	1131	39 1/8	1336	45 1/8	1485
33 1/4	1135	39 1/4	1340	45 1/4	1487
33 3/8	1140	39 3/8	1344	45 3/8	1489
33 1/2	1145	39 1/2	1347	45 1/2	1491
33 5/8	1149	39 5/8	1351	45 5/8	1493
33 3/4	1154	39 3/4	1355	45 3/4	1495
33 7/8	1158	39 7/8	1358	45 7/8	1497
34	1163	40	1362	46	1498
34 1/8	1168	40 1/8	1366	46 1/8	1500
34 1/4	1172	40 1/4	1369	46 1/4	1502
34 3/8	1177	40 3/8	1373	46 3/8	1503
34 1/2	1181	40 1/2	1376	46 1/2	1505
34 5/8	1186	40 5/8	1380	46 5/8	1506
34 3/4	1190	40 3/4	1383	46 3/4	1508
34 7/8	1195	40 7/8	1387	46 7/8	1509
35	1199	41	1390	47	1510
35 1/8	1203	41 1/8	1394	47 1/8	1511
35 1/4	1208	41 1/4	1397	47 1/4	1512
35 3/8	1212	41 3/8	1400	47 3/8	1513
35 1/2	1217	41 1/2	1404	47 1/2	1514
35 5/8	1221	41 5/8	1407	47 5/8	1514
35 3/4	1225	41 3/4	1410		
35 7/8	1230	41 7/8	1414		
36	1234	42	1417		



**CONTAINMENT**  
SOLUTIONS®

**HOW TO PROPERLY GAUGE YOUR TANK:**

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

**Water Paste Detection**

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

WATER FINDER #7686-1870

DAYCO/NATIONAL

DAYTON, OH

TEL: 1-800-283-2926

FAX: 1-800-688-4854

**Caution**

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

**ContainmentSolutions, Inc.**

5150 Jefferson Chemical Road

Conroe, TX 77301

Tel: 936-756-7731

Fax: 936-756-7766

**Note:** Calibration chart is based on the fluid level above a 5/16" deflector plate.