


**Model DWT6 (6) 2000 L  
DW FRP CUL Tank = 20,051Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	20	30.5	2234	60.5	5846	90.5	9997	120.5	14152
1.0	32	31.0	2286	61.0	5912	91.0	10068	121.0	14219
1.5	46	31.5	2339	61.5	5979	91.5	10138	121.5	14285
2.0	61	32.0	2392	62.0	6045	92.0	10209	122.0	14351
2.5	79	32.5	2445	62.5	6112	92.5	10280	122.5	14417
3.0	97	33.0	2499	63.0	6179	93.0	10350	123.0	14482
3.5	117	33.5	2553	63.5	6246	93.5	10421	123.5	14548
4.0	138	34.0	2607	64.0	6313	94.0	10491	124.0	14614
4.5	160	34.5	2661	64.5	6381	94.5	10562	124.5	14679
5.0	183	35.0	2716	65.0	6448	95.0	10633	125.0	14744
5.5	207	35.5	2771	65.5	6516	95.5	10703	125.5	14809
6.0	232	36.0	2827	66.0	6583	96.0	10774	126.0	14874
6.5	258	36.5	2883	66.5	6651	96.5	10844	126.5	14938
7.0	285	37.0	2939	67.0	6719	97.0	10914	127.0	15003
7.5	313	37.5	2995	67.5	6787	97.5	10985	127.5	15067
8.0	341	38.0	3052	68.0	6855	98.0	11055	128.0	15131
8.5	371	38.5	3109	68.5	6924	98.5	11126	128.5	15195
9.0	401	39.0	3166	69.0	6992	99.0	11196	129.0	15259
9.5	432	39.5	3224	69.5	7061	99.5	11266	129.5	15322
10.0	463	40.0	3281	70.0	7129	100.0	11337	130.0	15386
10.5	496	40.5	3339	70.5	7198	100.5	11407	130.5	15449
11.0	529	41.0	3398	71.0	7267	101.0	11477	131.0	15512
11.5	562	41.5	3456	71.5	7335	101.5	11547	131.5	15574
12.0	597	42.0	3515	72.0	7404	102.0	11617	132.0	15637
12.5	632	42.5	3574	72.5	7473	102.5	11687	132.5	15699
13.0	667	43.0	3634	73.0	7543	103.0	11757	133.0	15761
13.5	704	43.5	3693	73.5	7612	103.5	11827	133.5	15823
14.0	740	44.0	3753	74.0	7681	104.0	11897	134.0	15885
14.5	778	44.5	3813	74.5	7750	104.5	11966	134.5	15946
15.0	816	45.0	3873	75.0	7820	105.0	12036	135.0	16007
15.5	854	45.5	3934	75.5	7889	105.5	12106	135.5	16068
16.0	894	46.0	3995	76.0	7959	106.0	12175	136.0	16129
16.5	933	46.5	4056	76.5	8029	106.5	12245	136.5	16190
17.0	974	47.0	4117	77.0	8098	107.0	12314	137.0	16250
17.5	1014	47.5	4179	77.5	8168	107.5	12384	137.5	16310
18.0	1056	48.0	4240	78.0	8238	108.0	12453	138.0	16370
18.5	1097	48.5	4302	78.5	8308	108.5	12522	138.5	16429
19.0	1140	49.0	4364	79.0	8378	109.0	12591	139.0	16489
19.5	1183	49.5	4427	79.5	8448	109.5	12660	139.5	16548
20.0	1226	50.0	4489	80.0	8518	110.0	12729	140.0	16607
20.5	1270	50.5	4552	80.5	8588	110.5	12798	140.5	16665
21.0	1314	51.0	4615	81.0	8658	111.0	12867	141.0	16723
21.5	1358	51.5	4678	81.5	8728	111.5	12935	141.5	16781
22.0	1404	52.0	4742	82.0	8799	112.0	13004	142.0	16839
22.5	1449	52.5	4805	82.5	8869	112.5	13072	142.5	16897
23.0	1495	53.0	4869	83.0	8939	113.0	13141	143.0	16954
23.5	1542	53.5	4933	83.5	9010	113.5	13209	143.5	17011
24.0	1588	54.0	4997	84.0	9080	114.0	13277	144.0	17067
24.5	1636	54.5	5061	84.5	9150	114.5	13345	144.5	17124
25.0	1684	55.0	5126	85.0	9221	115.0	13413	145.0	17180
25.5	1732	55.5	5190	85.5	9291	115.5	13481	145.5	17235
26.0	1780	56.0	5255	86.0	9362	116.0	13549	146.0	17291
26.5	1829	56.5	5320	86.5	9432	116.5	13616	146.5	17346
27.0	1878	57.0	5385	87.0	9503	117.0	13684	147.0	17401
27.5	1928	57.5	5451	87.5	9574	117.5	13751	147.5	17455
28.0	1978	58.0	5516	88.0	9644	118.0	13818	148.0	17510
28.5	2029	58.5	5582	88.5	9715	118.5	13885	148.5	17563
29.0	2079	59.0	5647	89.0	9785	119.0	13952	149.0	17617
29.5	2131	59.5	5713	89.5	9856	119.5	14019	149.5	17670
30.0	2182	60.0	5779	90.0	9927	120.0	14086	150.0	17723

**Model DWT6 (6) 20000 L  
DW FRP CUL Tank = 20,051Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
150.5	17776	180.5	20023
151.0	17828	181.0	20035
151.5	17880	181.5	20045
152.0	17931	182.0	20051
152.5	17982		
153.0	18033		
153.5	18083		
154.0	18133		
154.5	18183		
155.0	18232		
155.5	18281		
156.0	18329		
156.5	18378		
157.0	18425		
157.5	18472		
158.0	18519		
158.5	18566		
159.0	18611		
159.5	18657		
160.0	18702		
160.5	18747		
161.0	18791		
161.5	18834		
162.0	18878		
162.5	18920		
163.0	18963		
163.5	19004		
164.0	19045		
164.5	19086		
165.0	19126		
165.5	19166		
166.0	19205		
166.5	19243		
167.0	19281		
167.5	19319		
168.0	19356		
168.5	19392		
169.0	19427		
169.5	19462		
170.0	19496		
170.5	19530		
171.0	19563		
171.5	19595		
172.0	19627		
172.5	19657		
173.0	19687		
173.5	19717		
174.0	19745		
174.5	19773		
175.0	19799		
175.5	19825		
176.0	19850		
176.5	19874		
177.0	19897		
177.5	19919		
178.0	19939		
178.5	19959		
179.0	19977		
179.5	19994		
180.0	20009		



**CONTAINMENT SOLUTIONS®**

**HOW TO PROPERLY GAUGE YOUR TANK:**  
 Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:  
 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.  
 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.  
 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

**Water Paste Detection:**  
 To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste  
 Federal Process Corp.  
 800-846-7325  
[www.gasoila.com](http://www.gasoila.com)

**Caution**  
 Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

**Containment Solutions, Inc.**  
 5150 Jefferson Chemical Road  
 Conroe, TX 77301  
 Tel: 936-756-7731  
 Fax: 936-756-7766

**Note:** Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.

*Pub No. CAL 6-20000DWT-CAN 5/11*