

**DWT6 6'-2000 COMPARTMENT
7,975 Liters**

06/22/2023

DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)
0.5	7	24.5	633	48.5	1,694	72.5	2,978
1.0	12	25.0	652	49.0	1,719	73.0	3,006
1.5	17	25.5	670	49.5	1,744	73.5	3,034
2.0	23	26.0	690	50.0	1,770	74.0	3,062
2.5	29	26.5	709	50.5	1,795	74.5	3,090
3.0	36	27.0	728	51.0	1,820	75.0	3,118
3.5	44	27.5	748	51.5	1,846	75.5	3,147
4.0	52	28.0	768	52.0	1,871	76.0	3,175
4.5	60	28.5	788	52.5	1,897	76.5	3,203
5.0	69	29.0	808	53.0	1,922	77.0	3,232
5.5	78	29.5	828	53.5	1,948	77.5	3,260
6.0	88	30.0	848	54.0	1,974	78.0	3,288
6.5	98	30.5	869	54.5	2,000	78.5	3,317
7.0	108	31.0	889	55.0	2,026	79.0	3,345
7.5	118	31.5	910	55.5	2,052	79.5	3,374
8.0	129	32.0	931	56.0	2,078	80.0	3,402
8.5	141	32.5	952	56.5	2,105	80.5	3,431
9.0	152	33.0	974	57.0	2,131	81.0	3,459
9.5	164	33.5	995	57.5	2,157	81.5	3,488
10.0	176	34.0	1,017	58.0	2,184	82.0	3,517
10.5	189	34.5	1,038	58.5	2,210	82.5	3,545
11.0	201	35.0	1,060	59.0	2,237	83.0	3,574
11.5	214	35.5	1,082	59.5	2,264	83.5	3,603
12.0	228	36.0	1,104	60.0	2,290	84.0	3,631
12.5	241	36.5	1,126	60.5	2,317	84.5	3,660
13.0	255	37.0	1,149	61.0	2,344	85.0	3,689
13.5	269	37.5	1,171	61.5	2,371	85.5	3,717
14.0	283	38.0	1,194	62.0	2,398	86.0	3,746
14.5	298	38.5	1,216	62.5	2,425	86.5	3,775
15.0	312	39.0	1,239	63.0	2,452	87.0	3,803
15.5	327	39.5	1,262	63.5	2,479	87.5	3,832
16.0	343	40.0	1,285	64.0	2,507	88.0	3,861
16.5	358	40.5	1,308	64.5	2,534	88.5	3,890
17.0	374	41.0	1,332	65.0	2,561	89.0	3,918
17.5	390	41.5	1,355	65.5	2,589	89.5	3,947
18.0	406	42.0	1,379	66.0	2,616	90.0	3,976
18.5	422	42.5	1,402	66.5	2,644	90.5	4,005
19.0	438	43.0	1,426	67.0	2,671	91.0	4,033
19.5	455	43.5	1,450	67.5	2,699	91.5	4,062
20.0	472	44.0	1,474	68.0	2,727	92.0	4,091
20.5	489	44.5	1,498	68.5	2,754	92.5	4,120
21.0	506	45.0	1,522	69.0	2,782	93.0	4,148
21.5	524	45.5	1,546	69.5	2,810	93.5	4,177
22.0	542	46.0	1,571	70.0	2,838	94.0	4,206
22.5	559	46.5	1,595	70.5	2,866	94.5	4,234
23.0	578	47.0	1,620	71.0	2,893	95.0	4,263
23.5	596	47.5	1,645	71.5	2,921	95.5	4,292
24.0	614	48.0	1,669	72.0	2,949	96.0	4,321

DWT6 6'-2000 COMPARTMENT
7,975 Liters

06/22/2023

DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)
96.5	4,349	120.5	5,690	144.5	6,875	168.5	7,750
97.0	4,378	121.0	5,716	145.0	6,897	169.0	7,763
97.5	4,407	121.5	5,743	145.5	6,919	169.5	7,776
98.0	4,435	122.0	5,770	146.0	6,941	170.0	7,789
98.5	4,464	122.5	5,796	146.5	6,963	170.5	7,801
99.0	4,492	123.0	5,823	147.0	6,984	171.0	7,813
99.5	4,521	123.5	5,849	147.5	7,006	171.5	7,825
100.0	4,549	124.0	5,875	148.0	7,027	172.0	7,837
100.5	4,578	124.5	5,902	148.5	7,048	172.5	7,848
101.0	4,607	125.0	5,928	149.0	7,069	173.0	7,859
101.5	4,635	125.5	5,954	149.5	7,090	173.5	7,869
102.0	4,663	126.0	5,980	150.0	7,110	174.0	7,880
102.5	4,692	126.5	6,006	150.5	7,131	174.5	7,889
103.0	4,720	127.0	6,032	151.0	7,151	175.0	7,899
103.5	4,749	127.5	6,057	151.5	7,171	175.5	7,908
104.0	4,777	128.0	6,083	152.0	7,191	176.0	7,917
104.5	4,805	128.5	6,109	152.5	7,211	176.5	7,925
105.0	4,834	129.0	6,134	153.0	7,231	177.0	7,933
105.5	4,862	129.5	6,160	153.5	7,251	177.5	7,940
106.0	4,890	130.0	6,185	154.0	7,270	178.0	7,947
106.5	4,918	130.5	6,210	154.5	7,289	178.5	7,954
107.0	4,947	131.0	6,235	155.0	7,308	179.0	7,959
107.5	4,975	131.5	6,260	155.5	7,327	179.5	7,964
108.0	5,003	132.0	6,285	156.0	7,346	180.0	7,969
108.5	5,031	132.5	6,310	156.5	7,364	180.5	7,972
109.0	5,059	133.0	6,335	157.0	7,383	181.0	7,975
109.5	5,087	133.5	6,360	157.5	7,401		
110.0	5,115	134.0	6,384	158.0	7,419		
110.5	5,143	134.5	6,409	158.5	7,437		
111.0	5,171	135.0	6,433	159.0	7,455		
111.5	5,198	135.5	6,457	159.5	7,472		
112.0	5,226	136.0	6,482	160.0	7,489		
112.5	5,254	136.5	6,506	160.5	7,506		
113.0	5,281	137.0	6,530	161.0	7,523		
113.5	5,309	137.5	6,554	161.5	7,540		
114.0	5,337	138.0	6,577	162.0	7,556		
114.5	5,364	138.5	6,601	162.5	7,573		
115.0	5,392	139.0	6,624	163.0	7,589		
115.5	5,419	139.5	6,648	163.5	7,604		
116.0	5,446	140.0	6,671	164.0	7,620		
116.5	5,474	140.5	6,694	164.5	7,635		
117.0	5,501	141.0	6,717	165.0	7,651		
117.5	5,528	141.5	6,740	165.5	7,666		
118.0	5,555	142.0	6,763	166.0	7,680		
118.5	5,582	142.5	6,786	166.5	7,695		
119.0	5,609	143.0	6,808	167.0	7,709		
119.5	5,636	143.5	6,831	167.5	7,723		
120.0	5,663	144.0	6,853	168.0	7,737		

Fiber Glass Systems



HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

Kolor Kut Water Finding Paste Description - PASTE02 - for Salt and Chloride Solutions
7915 East Elm Street
Houston, TX 77012
Phone (713) 926-4780
E-Mail Sales@KolorKut.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

NOV - Fiber Glass Systems - Containment Solutions™ Tanks

500 Conroe Park Drive West
Conroe, TX 77303
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.