


Model DWT6 (6) 25000 L
DW FRP CUL Tank = 25,623Liters

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	25	30.5	2868	60.5	7483	90.5	12776	120.5	18073
1.0	41	31.0	2935	61.0	7567	91.0	12866	121.0	18158
1.5	59	31.5	3002	61.5	7652	91.5	12956	121.5	18242
2.0	79	32.0	3070	62.0	7737	92.0	13046	122.0	18327
2.5	101	32.5	3138	62.5	7823	92.5	13136	122.5	18411
3.0	125	33.0	3206	63.0	7908	93.0	13226	123.0	18495
3.5	151	33.5	3275	63.5	7994	93.5	13316	123.5	18578
4.0	178	34.0	3345	64.0	8079	94.0	13406	124.0	18662
4.5	206	34.5	3415	64.5	8165	94.5	13496	124.5	18745
5.0	236	35.0	3485	65.0	8251	95.0	13585	125.0	18828
5.5	267	35.5	3555	65.5	8337	95.5	13675	125.5	18911
6.0	299	36.0	3626	66.0	8424	96.0	13765	126.0	18994
6.5	332	36.5	3698	66.5	8510	96.5	13855	126.5	19076
7.0	367	37.0	3770	67.0	8597	97.0	13945	127.0	19159
7.5	403	37.5	3842	67.5	8684	97.5	14035	127.5	19241
8.0	439	38.0	3914	68.0	8771	98.0	14124	128.0	19322
8.5	477	38.5	3987	68.5	8858	98.5	14214	128.5	19404
9.0	516	39.0	4060	69.0	8945	99.0	14304	129.0	19485
9.5	556	39.5	4134	69.5	9032	99.5	14393	129.5	19566
10.0	596	40.0	4208	70.0	9120	100.0	14483	130.0	19647
10.5	638	40.5	4282	70.5	9207	100.5	14572	130.5	19728
11.0	680	41.0	4356	71.0	9295	101.0	14662	131.0	19808
11.5	724	41.5	4431	71.5	9383	101.5	14751	131.5	19888
12.0	768	42.0	4506	72.0	9471	102.0	14840	132.0	19968
12.5	813	42.5	4582	72.5	9559	102.5	14930	132.5	20048
13.0	859	43.0	4658	73.0	9647	103.0	15019	133.0	20127
13.5	905	43.5	4734	73.5	9735	103.5	15108	133.5	20206
14.0	952	44.0	4811	74.0	9823	104.0	15197	134.0	20285
14.5	1001	44.5	4887	74.5	9912	104.5	15286	134.5	20363
15.0	1049	45.0	4964	75.0	10000	105.0	15375	135.0	20442
15.5	1099	45.5	5042	75.5	10089	105.5	15463	135.5	20520
16.0	1149	46.0	5120	76.0	10178	106.0	15552	136.0	20597
16.5	1200	46.5	5198	76.5	10266	106.5	15641	136.5	20675
17.0	1252	47.0	5276	77.0	10355	107.0	15729	137.0	20752
17.5	1304	47.5	5354	77.5	10444	107.5	15818	137.5	20828
18.0	1357	48.0	5433	78.0	10533	108.0	15906	138.0	20905
18.5	1411	48.5	5512	78.5	10622	108.5	15994	138.5	20981
19.0	1465	49.0	5592	79.0	10712	109.0	16082	139.0	21057
19.5	1520	49.5	5671	79.5	10801	109.5	16170	139.5	21132
20.0	1576	50.0	5751	80.0	10890	110.0	16258	140.0	21207
20.5	1632	50.5	5831	80.5	10980	110.5	16346	140.5	21282
21.0	1688	51.0	5912	81.0	11069	111.0	16434	141.0	21357
21.5	1746	51.5	5992	81.5	11159	111.5	16521	141.5	21431
22.0	1804	52.0	6073	82.0	11248	112.0	16609	142.0	21505
22.5	1862	52.5	6154	82.5	11338	112.5	16696	142.5	21578
23.0	1921	53.0	6236	83.0	11427	113.0	16783	143.0	21651
23.5	1981	53.5	6317	83.5	11517	113.5	16870	143.5	21724
24.0	2041	54.0	6399	84.0	11607	114.0	16957	144.0	21797
24.5	2101	54.5	6481	84.5	11696	114.5	17044	144.5	21869
25.0	2162	55.0	6564	85.0	11786	115.0	17130	145.0	21940
25.5	2224	55.5	6646	85.5	11876	115.5	17217	145.5	22012
26.0	2286	56.0	6729	86.0	11966	116.0	17303	146.0	22083
26.5	2349	56.5	6812	86.5	12056	116.5	17389	146.5	22153
27.0	2412	57.0	6895	87.0	12146	117.0	17475	147.0	22223
27.5	2476	57.5	6978	87.5	12236	117.5	17561	147.5	22293
28.0	2540	58.0	7062	88.0	12326	118.0	17647	148.0	22362
28.5	2605	58.5	7146	88.5	12416	118.5	17733	148.5	22431
29.0	2670	59.0	7230	89.0	12506	119.0	17818	149.0	22500
29.5	2735	59.5	7314	89.5	12596	119.5	17903	149.5	22568
30.0	2801	60.0	7398	90.0	12686	120.0	17988	150.0	22636

**Model DWT6 (6) 25000 L
DW FRP CUL Tank = 25,623Liters**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
150.5	22703	180.5	25588
151.0	22770	181.0	25603
151.5	22836	181.5	25615
152.0	22902	182.0	25623
152.5	22967		
153.0	23032		
153.5	23097		
154.0	23161		
154.5	23225		
155.0	23288		
155.5	23350		
156.0	23412		
156.5	23474		
157.0	23535		
157.5	23595		
158.0	23655		
158.5	23715		
159.0	23774		
159.5	23832		
160.0	23890		
160.5	23947		
161.0	24004		
161.5	24060		
162.0	24115		
162.5	24170		
163.0	24224		
163.5	24278		
164.0	24331		
164.5	24383		
165.0	24434		
165.5	24485		
166.0	24535		
166.5	24585		
167.0	24633		
167.5	24681		
168.0	24729		
168.5	24775		
169.0	24821		
169.5	24866		
170.0	24910		
170.5	24953		
171.0	24995		
171.5	25036		
172.0	25077		
172.5	25116		
173.0	25155		
173.5	25193		
174.0	25229		
174.5	25265		
175.0	25299		
175.5	25332		
176.0	25364		
176.5	25395		
177.0	25425		
177.5	25453		
178.0	25480		
178.5	25505		
179.0	25528		
179.5	25550		
180.0	25570		



CONTAINMENT SOLUTIONS®

HOW TO PROPERLY GAUGE YOUR TANK:
Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:
1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection:
To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste
Federal Process Corp.
800-846-7325
www.gasoila.com

Caution
Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

Containment Solutions, Inc.
5150 Jefferson Chemical Road
Conroe, TX 77301
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.

[Pub No. CAL 6-25000DWT-CAN 5/11](#)