

DWT6 6'-2500 COMPARTMENT
10,179 Liters

06/22/2023

DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)
0.5	11	24.5	827	48.5	2,188	72.5	3,822
1.0	18	25.0	851	49.0	2,220	73.0	3,858
1.5	25	25.5	875	49.5	2,252	73.5	3,893
2.0	33	26.0	900	50.0	2,284	74.0	3,929
2.5	41	26.5	925	50.5	2,316	74.5	3,965
3.0	51	27.0	950	51.0	2,349	75.0	4,001
3.5	61	27.5	975	51.5	2,381	75.5	4,037
4.0	71	28.0	1,000	52.0	2,414	76.0	4,073
4.5	82	28.5	1,026	52.5	2,446	76.5	4,109
5.0	94	29.0	1,052	53.0	2,479	77.0	4,145
5.5	106	29.5	1,078	53.5	2,512	77.5	4,181
6.0	119	30.0	1,104	54.0	2,545	78.0	4,217
6.5	132	30.5	1,130	54.5	2,578	78.5	4,253
7.0	145	31.0	1,157	55.0	2,611	79.0	4,289
7.5	159	31.5	1,184	55.5	2,645	79.5	4,325
8.0	173	32.0	1,211	56.0	2,678	80.0	4,361
8.5	188	32.5	1,238	56.5	2,711	80.5	4,398
9.0	203	33.0	1,265	57.0	2,745	81.0	4,434
9.5	219	33.5	1,293	57.5	2,778	81.5	4,470
10.0	235	34.0	1,320	58.0	2,812	82.0	4,507
10.5	251	34.5	1,348	58.5	2,846	82.5	4,543
11.0	267	35.0	1,376	59.0	2,880	83.0	4,579
11.5	284	35.5	1,404	59.5	2,914	83.5	4,616
12.0	302	36.0	1,433	60.0	2,948	84.0	4,652
12.5	319	36.5	1,461	60.5	2,982	84.5	4,688
13.0	337	37.0	1,490	61.0	3,016	85.0	4,725
13.5	355	37.5	1,519	61.5	3,051	85.5	4,761
14.0	374	38.0	1,547	62.0	3,085	86.0	4,798
14.5	393	38.5	1,577	62.5	3,119	86.5	4,834
15.0	412	39.0	1,606	63.0	3,154	87.0	4,870
15.5	431	39.5	1,635	63.5	3,189	87.5	4,907
16.0	451	40.0	1,665	64.0	3,223	88.0	4,943
16.5	471	40.5	1,695	64.5	3,258	88.5	4,980
17.0	492	41.0	1,724	65.0	3,293	89.0	5,016
17.5	512	41.5	1,754	65.5	3,328	89.5	5,053
18.0	533	42.0	1,784	66.0	3,363	90.0	5,089
18.5	554	42.5	1,815	66.5	3,397	90.5	5,126
19.0	575	43.0	1,845	67.0	3,433	91.0	5,162
19.5	597	43.5	1,876	67.5	3,468	91.5	5,199
20.0	619	44.0	1,906	68.0	3,503	92.0	5,235
20.5	641	44.5	1,937	68.5	3,538	92.5	5,272
21.0	663	45.0	1,968	69.0	3,573	93.0	5,308
21.5	686	45.5	1,999	69.5	3,609	93.5	5,345
22.0	709	46.0	2,030	70.0	3,644	94.0	5,381
22.5	732	46.5	2,062	70.5	3,680	94.5	5,417
23.0	755	47.0	2,093	71.0	3,715	95.0	5,454
23.5	779	47.5	2,125	71.5	3,751	95.5	5,490
24.0	803	48.0	2,156	72.0	3,786	96.0	5,527

DWT6 6'-2500 COMPARTMENT
10,179 Liters

06/22/2023

DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)	DIPSTICK (cm)	VOLUME (L)
96.5	5,563	120.5	7,265	144.5	8,776	168.5	9,898
97.0	5,599	121.0	7,299	145.0	8,804	169.0	9,915
97.5	5,636	121.5	7,333	145.5	8,832	169.5	9,932
98.0	5,672	122.0	7,367	146.0	8,860	170.0	9,948
98.5	5,708	122.5	7,401	146.5	8,888	170.5	9,964
99.0	5,745	123.0	7,434	147.0	8,915	171.0	9,979
99.5	5,781	123.5	7,468	147.5	8,943	171.5	9,995
100.0	5,817	124.0	7,501	148.0	8,970	172.0	10,009
100.5	5,853	124.5	7,535	148.5	8,997	172.5	10,024
101.0	5,890	125.0	7,568	149.0	9,023	173.0	10,038
101.5	5,926	125.5	7,601	149.5	9,050	173.5	10,051
102.0	5,962	126.0	7,634	150.0	9,077	174.0	10,065
102.5	5,998	126.5	7,667	150.5	9,103	174.5	10,077
103.0	6,034	127.0	7,700	151.0	9,129	175.0	10,089
103.5	6,070	127.5	7,733	151.5	9,155	175.5	10,101
104.0	6,106	128.0	7,766	152.0	9,180	176.0	10,112
104.5	6,142	128.5	7,798	152.5	9,206	176.5	10,123
105.0	6,178	129.0	7,831	153.0	9,231	177.0	10,133
105.5	6,214	129.5	7,863	153.5	9,256	177.5	10,142
106.0	6,250	130.0	7,895	154.0	9,281	178.0	10,151
106.5	6,285	130.5	7,927	154.5	9,306	178.5	10,159
107.0	6,321	131.0	7,960	155.0	9,330	179.0	10,167
107.5	6,357	131.5	7,991	155.5	9,354	179.5	10,173
108.0	6,393	132.0	8,023	156.0	9,378	180.0	10,179
108.5	6,428	132.5	8,055	156.5	9,402		
109.0	6,464	133.0	8,087	157.0	9,426		
109.5	6,499	133.5	8,118	157.5	9,449		
110.0	6,535	134.0	8,149	158.0	9,472		
110.5	6,570	134.5	8,180	158.5	9,495		
111.0	6,605	135.0	8,212	159.0	9,518		
111.5	6,641	135.5	8,243	159.5	9,540		
112.0	6,676	136.0	8,273	160.0	9,562		
112.5	6,711	136.5	8,304	160.5	9,584		
113.0	6,746	137.0	8,335	161.0	9,606		
113.5	6,781	137.5	8,365	161.5	9,627		
114.0	6,816	138.0	8,395	162.0	9,649		
114.5	6,851	138.5	8,425	162.5	9,670		
115.0	6,886	139.0	8,455	163.0	9,690		
115.5	6,921	139.5	8,485	163.5	9,710		
116.0	6,956	140.0	8,515	164.0	9,731		
116.5	6,990	140.5	8,545	164.5	9,750		
117.0	7,025	141.0	8,574	165.0	9,770		
117.5	7,060	141.5	8,603	165.5	9,789		
118.0	7,094	142.0	8,633	166.0	9,808		
118.5	7,128	142.5	8,662	166.5	9,827		
119.0	7,163	143.0	8,690	167.0	9,845		
119.5	7,197	143.5	8,719	167.5	9,863		
120.0	7,231	144.0	8,748	168.0	9,881		

Fiber Glass Systems



HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. However, some water detection paste cannot detect antifreeze mixtures. If antifreeze mixtures are used for the cavity monitoring fluid, the following product is capable of detecting water or antifreeze (brine or up to 50 percent glycol) solution in the tank water bottoms:

Kolor Kut Water Finding Paste Description - PASTE02 - for Salt and Chloride Solutions
7915 East Elm Street
Houston, TX 77012
Phone (713) 926-4780
E-Mail Sales@KolorKut.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.

NOV - Fiber Glass Systems - Containment Solutions™ Tanks

500 Conroe Park Drive West
Conroe, TX 77303
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 5/16" deflector plate.