


TYPICAL 42" WATER BASIN



GENERAL NOTES:

1. THE STANDARD WATER BASIN IS 42" I.D., AND SHALL BE SUPPLIED BY THE TANK MANUFACTURER (36" THROUGH 120" DIAMETER PUMP VAULTS ARE OPTIONAL).
2. FIBERGLASS TOP SHALL BE FACTORY INSTALLED TO ACCOMMODATE OPTIONAL CONTRACTOR SUPPLIED ALUMINUM HATCH COVER.
3. BOTTOM FIBERGLASS ANTI-FLOTATION RING SHALL BE FACTORY INSTALLED.
4. ALL FRP NOZZLES SHALL BE FLAT-FACED, FLANGED AND CONFORM TO ANSI B16.5 150 POUND BOLTING PATTERNS.
5. FLEXIBLE CONNECTORS MUST BE USED ON ALL PIPING CONNECTIONS, INCLUDES FITTINGS AND FLANGED NOZZLES. PIPING MUST BE FREE TO MOVE INDEPENDENT OF THE TANK AND PUMP VAULT.
6. WATER BASINS SHALL BE FRP.
7. WATER BASINS SHALL BE INSTALLED ACCORDING TO THE CONTAINMENT SOLUTIONS SUPPLEMENTAL INSTALLATION INSTRUCTIONS IN EFFECT AT TIME OF INSTALLATION.



CONTAINMENT
SOLUTIONS®