

*Are Your Tank
Sumps Tight?*

TESTABLE SUMP LIDS FROM CSI

Underground storage tank regulations in some areas require tank sumps to be periodically tested for tightness. These regulations often require the entire sump including lid, joints and piping penetrations be tested after installation and over the lifetime of the system.

In response to these regulations, Containment Solutions can provide a watertight and testable lid designed to fit on CSI watertight sumps. To retrofit models in the field, contact CSI Field Services at 800-822-1997.



WTL TEST KIT INCLUDES:

- Vacuum Gun
- Vacuum Gauge
- Grounding Kit
- Thermometer
- Test Procedure



**USE THE CSI TEST PROCEDURE
AND KNOW YOUR TANK SUMPS
ARE TIGHT**

The FRP watertight lid has an outside diameter of 32" or 37" and is designed for high water table conditions. The lid is manufactured with a non-skid exterior surface and securely slips over an o-ring seal. This eliminates the need for metal hardware and latches.

The lid contains quick connect fittings for the vacuum gun and gauge. Also, included is a bi-metal thermometer to monitor temperature change during the test.

For a copy of the CSI vacuum test procedure, contact your local CSI representative at 1-800-537-4730.



CONTAINMENT SOLUTIONS, INC. • 5150 Jefferson Chemical Rd • Conroe, TX 77301-6834
Toll Free (877) CSI - TANK or (936) 756-7731 • Fax (936) 756-7766
www.containmentsolutions.com

PEI
PETROLEUM EQUIPMENT INSTITUTE

UL
LISTED